

**PROFESSIONAL RUBBERIZED COATING AERO**

Version 3.0

Revision Date 06/29/2017

Print Date 10/30/2017

**SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Material name : PROFESSIONAL RUBBERIZED COATING AERO

Material number : 00000000000028900

**Manufacturer or supplier's details**

Company : Zep Inc.

Address : 1310 Seaboard Industrial Blvd., NW  
Atlanta, GA 30318

Telephone : 404-352-1680

**Emergency telephone numbers**
**For SDS Information** : Compliance Services 1-877-428-9937

**For a Medical Emergency** : 877-541-2016 Toll Free - All Calls Recorded

**For a Transportation Emergency** : CHEMTREC: 800-424-9300 - All Calls Recorded.  
In the District of Columbia 202-483-7616

**Recommended use of the chemical and restrictions on use**

Recommended use : Protective Coating

**SECTION 2. HAZARDS IDENTIFICATION**
**Emergency Overview**

Appearance	Aerosol containing a liquefied gas
Colour	black
Odour	solvent-like

**GHS Classification**

Flammable aerosols : Category 1  
 Gases under pressure : Liquefied gas  
 Skin irritation : Category 2  
 Eye irritation : Category 2A  
 Reproductive toxicity : Category 2  
 Specific target organ toxicity - single exposure : Category 3 (Central nervous system)  
 Specific target organ toxicity - repeated exposure (Inhalation) : Category 2  
 Aspiration hazard : Category 1

**GHS label elements**

Hazard pictograms :



Signal word : Danger

**PROFESSIONAL RUBBERIZED COATING AERO**

Version 3.0

Revision Date 06/29/2017

Print Date 10/30/2017

- Hazard statements : H222 Extremely flammable aerosol.  
H280 Contains gas under pressure; may explode if heated.  
H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.  
H361 Suspected of damaging fertility or the unborn child.  
H373 May cause damage to organs through prolonged or repeated exposure if inhaled.
- Precautionary statements : **Prevention:**  
P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Pressurized container: Do not pierce or burn, even after use.  
P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.  
P264 Wash skin thoroughly after handling.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.  
**Response:**  
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.  
P302 + P352 IF ON SKIN: Wash with plenty of soap and water.  
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308 + P313 IF exposed or concerned: Get medical advice/ attention.  
P331 Do NOT induce vomiting.  
P332 + P313 If skin irritation occurs: Get medical advice/ attention.  
P337 + P313 If eye irritation persists: Get medical advice/ attention.  
P362 Take off contaminated clothing and wash before reuse.  
**Storage:**  
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.  
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.  
**Disposal:**  
Dispose of contents/container in accordance with local regulation.

---

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

**Hazardous components**

**PROFESSIONAL RUBBERIZED COATING AERO**

Version 3.0

Revision Date 06/29/2017

Print Date 10/30/2017

Chemical name	CAS-No.	Concentration [%]
acetone	67-64-1	>= 30 - < 50
toluene	108-88-3	>= 10 - < 20
isobutane	75-28-5	>= 10 - < 20
propane	74-98-6	>= 5 - < 10
Calcium carbonate	1317-65-3	>= 5 - < 10

The exact percentages of disclosed substances are withheld as trade secrets.

**SECTION 4. FIRST AID MEASURES**

- General advice : Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Symptoms of poisoning may appear several hours later.  
Do not leave the victim unattended.
- If inhaled : Consult a physician after significant exposure.  
If unconscious place in recovery position and seek medical advice.
- In case of skin contact : If skin irritation persists, call a physician.  
Wash off immediately with plenty of water for at least 15 minutes.  
If on clothes, remove clothes.
- In case of eye contact : Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.  
Rinse immediately with plenty of water for at least 15 minutes.
- If swallowed : Keep respiratory tract clear.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.  
DO NOT induce vomiting unless directed to do so by a physician or poison control center.  
Take victim immediately to hospital.
- Most important symptoms and effects, both acute and delayed : Aspiration may cause pulmonary oedema and pneumonitis.  
Symptoms may include shortness of breath, dry cough, and irritation of the nose, eyes, lips, mouth, and throat.  
Chronic effects are delayed and symptoms may not be observed during an exposure.  
Effects are dependent on exposure (dose, concentration, contact time).  
May be fatal if swallowed and enters airways.  
Suspected of damaging fertility or the unborn child.  
Review section 2 of SDS to see all potential hazards.
- Notes to physician : Treat symptomatically. Symptoms may be delayed.

**SECTION 5. FIREFIGHTING MEASURES**

- Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)

**PROFESSIONAL RUBBERIZED COATING AERO**

Version 3.0

Revision Date 06/29/2017

Print Date 10/30/2017

Dry chemical

- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : Carbon dioxide (CO<sub>2</sub>)  
Carbon monoxide  
Smoke
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
For safety reasons in case of fire, cans should be stored separately in closed containments.  
Use a water spray to cool fully closed containers.
- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Ensure adequate ventilation.  
Remove all sources of ignition.  
Evacuate personnel to safe areas.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
- Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Sweep up or vacuum up spillage and collect in suitable container for disposal.

**SECTION 7. HANDLING AND STORAGE**

- Advice on safe handling : Do not breathe vapours or spray mist.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharges.

**PROFESSIONAL RUBBERIZED COATING AERO**

Version 3.0

Revision Date 06/29/2017

Print Date 10/30/2017

Provide sufficient air exchange and/or exhaust in work rooms.  
Always replace cap after use.  
Dispose of rinse water in accordance with local and national regulations.

Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects.  
No smoking.  
Keep in a dry, cool and well-ventilated place.  
Observe label precautions.  
Electrical installations / working materials must comply with the technological safety standards.

Materials to avoid : Store and keep away from, oxidizing agents and acids.

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**
**Components with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
acetone	67-64-1	TWA	250 ppm	ACGIH
		STEL	500 ppm	ACGIH
		TWA	250 ppm 590 mg/m <sup>3</sup>	NIOSH REL
		TWA	1,000 ppm 2,400 mg/m <sup>3</sup>	OSHA Z-1
		TWA	750 ppm 1,800 mg/m <sup>3</sup>	OSHA P0
		STEL	1,000 ppm 2,400 mg/m <sup>3</sup>	OSHA P0
		STEL	750 ppm 1,780 mg/m <sup>3</sup>	CAL PEL
		C	3,000 ppm	CAL PEL
		PEL	500 ppm 1,200 mg/m <sup>3</sup>	CAL PEL
		toluene	108-88-3	TWA
TWA	100 ppm 375 mg/m <sup>3</sup>			NIOSH REL
ST	150 ppm 560 mg/m <sup>3</sup>			NIOSH REL
TWA	200 ppm			OSHA Z-2
CEIL	300 ppm			OSHA Z-2
Peak	500 ppm			OSHA Z-2
TWA	100 ppm 375 mg/m <sup>3</sup>			OSHA P0
STEL	150 ppm 560 mg/m <sup>3</sup>			OSHA P0
PEL	10 ppm 37 mg/m <sup>3</sup>			CAL PEL
		C	500 ppm	CAL PEL

## PROFESSIONAL RUBBERIZED COATING AERO

Version 3.0

Revision Date 06/29/2017

Print Date 10/30/2017

		STEL	150 ppm 560 mg/m <sup>3</sup>	CAL PEL
isobutane	75-28-5	TWA	800 ppm 1,900 mg/m <sup>3</sup>	NIOSH REL
propane	74-98-6	TWA	1,000 ppm	ACGIH
		TWA	1,000 ppm 1,800 mg/m <sup>3</sup>	NIOSH REL
		TWA	1,000 ppm 1,800 mg/m <sup>3</sup>	OSHA Z-1
		TWA	1,000 ppm 1,800 mg/m <sup>3</sup>	OSHA P0
		PEL	1,000 ppm 1,800 mg/m <sup>3</sup>	CAL PEL
Calcium carbonate	1317-65-3	TWA (Respirable)	5 mg/m <sup>3</sup>	NIOSH REL
		TWA (total)	10 mg/m <sup>3</sup>	NIOSH REL
		TWA (Respirable)	5 mg/m <sup>3</sup>	NIOSH REL
		TWA (total)	10 mg/m <sup>3</sup>	NIOSH REL
		TWA (Respirable)	5 mg/m <sup>3</sup>	NIOSH REL
		TWA (total)	10 mg/m <sup>3</sup>	NIOSH REL
		TWA (total dust)	15 mg/m <sup>3</sup>	OSHA Z-1
		TWA (respirable fraction)	5 mg/m <sup>3</sup>	OSHA Z-1
		TWA (Total dust)	15 mg/m <sup>3</sup>	OSHA P0
		TWA (respirable dust fraction)	5 mg/m <sup>3</sup>	OSHA P0

## Biological occupational exposure limits

Component	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
2-PROPANONE	67-64-1	Acetone	Urine	End of shift (As soon as possible after exposure ceases)	25 mg/l	ACGIH BEI
METHYLBENZENE	108-88-3	Toluene	In blood	Prior to last shift of workweek	0.02 mg/l	ACGIH BEI
METHYLBENZENE		Toluene	Urine	End of shift (As soon as possible after exposure ceases)	0.03 mg/l	ACGIH BEI
METHYLBENZENE		o-Cresol	Urine	End of shift (As	0.3.mg/g Creatinine	ACGIH BEI

**PROFESSIONAL RUBBERIZED COATING AERO**

Version 3.0

Revision Date 06/29/2017

Print Date 10/30/2017

				soon as possible after exposure ceases)		
--	--	--	--	---	--	--

**Engineering measures** : effective ventilation in all processing areas

**Personal protective equipment**

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection

Material

: Protective gloves

Remarks

: The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection

: Ensure that eyewash stations and safety showers are close to the workstation location.

Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing problems.

Skin and body protection

: Impervious clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures

: When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

---

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : Aerosol containing a liquefied gas

Colour : black

Odour : solvent-like

Odour Threshold : No data available

pH : Not applicable

Melting point/freezing point : No data available

Boiling point : 39.48 °C

Flash point : -73 °C

Evaporation rate : No data available

Flammability (solid, gas) : Extremely flammable aerosol.

Method: Third Party Data - Actual or Inferred

**PROFESSIONAL RUBBERIZED COATING AERO**

Version 3.0

Revision Date 06/29/2017

Print Date 10/30/2017

Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: 261,043.78 hPa (21 °C)
Relative vapour density	: No data available
Density	: 0.531 g/cm <sup>3</sup>
Solubility(ies)	
Water solubility	: No data available
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: 480.39 °C
Thermal decomposition	: No data available
Viscosity	
Viscosity, kinematic	: No data available
Heat of combustion	: 22.78 kJ/g

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity	: Stable
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Vapours may form explosive mixture with air. No decomposition if stored and applied as directed.
Conditions to avoid	: Heat, flames and sparks. Extremes of temperature and direct sunlight.
Incompatible materials	: Strong oxidizing agents Acids Nitrates Chlorine Fluorine
Hazardous decomposition products	: Carbon oxides

**SECTION 11. TOXICOLOGICAL INFORMATION****Potential Health Effects**

Aggravated Medical Condition	: None known.
Symptoms of Overexposure	: Aspiration may cause pulmonary oedema and pneumonitis. Symptoms may include shortness of breath, dry cough, and



**PROFESSIONAL RUBBERIZED COATING AERO**

Version 3.0

Revision Date 06/29/2017

Print Date 10/30/2017

irritation of the nose, eyes, lips, mouth, and throat.  
Chronic effects are delayed and symptoms may not be observed during an exposure.  
Effects are dependent on exposure (dose, concentration, contact time).

**Carcinogenicity:**

<b>IARC</b>	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
<b>ACGIH</b>	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.
<b>OSHA</b>	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.
<b>NTP</b>	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

**Acute toxicity****Components:****acetone:**

Acute oral toxicity	: LD50 Rat: 5,800 mg/kg
Acute inhalation toxicity	: LC50 Rat: 132 mg/l Exposure time: 3 h  LC50 Rat: 50.1 mg/l
Acute dermal toxicity	: LD50 Guinea pig: > 7,426 mg/kg  LD50 Rabbit: > 7,426 mg/kg

**Skin corrosion/irritation****Product:**

Remarks: Irritating to skin.

**Serious eye damage/eye irritation****Product:**

Remarks: Severe eye irritation

**Respiratory or skin sensitisation**

No data available

**Germ cell mutagenicity**

No data available

**PROFESSIONAL RUBBERIZED COATING AERO**

Version 3.0

Revision Date 06/29/2017

Print Date 10/30/2017

**Carcinogenicity**

No data available

**Reproductive toxicity**

No data available

**STOT - single exposure**

No data available

**STOT - repeated exposure**

No data available

**Aspiration toxicity****Product:**

May be fatal if swallowed and enters airways.

**Further information****Product:**

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

**Components:****toluene:**

Remarks: No data available

---

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity**

No data available

**Persistence and degradability**

No data available

**Bioaccumulative potential****Product:**Partition coefficient: n- : Remarks: No data available  
octanol/water**Components:****toluene :**Partition coefficient: n- : Pow: 2.73  
octanol/water**Mobility in soil**

No data available

**PROFESSIONAL RUBBERIZED COATING AERO**

Version 3.0

Revision Date 06/29/2017

Print Date 10/30/2017

**Other adverse effects**

No data available

**Product:**

Regulation 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : No data available

**Components:****toluene :**

Additional ecological information : No data available

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

Waste from residues : Do not dispose of waste into sewer.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Dispose of in accordance with local regulations.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

**SECTION 14. TRANSPORT INFORMATION**

Transportation Regulation: 49 CFR (USA):  
ORM-D, CONSUMER COMMODITY

Transportation Regulation: IMDG (Vessel):  
UN1950, AEROSOLS, 2.1, - Limited quantity

Transportation Regulation: IATA (Cargo Air):  
UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: IATA (Passenger Air):  
UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: TDG (Canada):  
UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

**PROFESSIONAL RUBBERIZED COATING AERO**

Version 3.0

Revision Date 06/29/2017

Print Date 10/30/2017

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

**SECTION 15. REGULATORY INFORMATION**

**TSCA list** : No substances are subject to a Significant New Use Rule.  
No substances are subject to TSCA 12(b) export notification requirements.

**EPCRA - Emergency Planning and Community Right-to-Know Act**
**CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
toluene	108-88-3	1000	*

\*: Calculated RQ exceeds reasonably attainable upper limit.

**SARA 304 Extremely Hazardous Substances Reportable Quantity**

This material does not contain any components with a section 304 EHS RQ.

**SARA 311/312 Hazards** : Fire Hazard  
Sudden Release of Pressure Hazard  
Acute Health Hazard  
Chronic Health Hazard

**SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:

toluene	108-88-3	15 %
---------	----------	------

**California Prop 65** WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

toluene	108-88-3
4-methylpentan-2-one	108-10-1

WARNING! This product contains a chemical known to the State of California to cause cancer.

4-methylpentan-2-one	108-10-1
carbon black	1333-86-4

**The components of this product are reported in the following inventories:**

**TSCA** On TSCA Inventory  
**DSL** This product contains one or more components that are listed on the Canadian NDSL. All other components are on the Canadian DSL.

**PROFESSIONAL RUBBERIZED COATING AERO**

Version 3.0


Revision Date 06/29/2017

Print Date 10/30/2017

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

**Inventory Acronym and Validity Area Legend:**

TSCA (USA), DSL (Canada), NDSL (Canada)

**SECTION 16. OTHER INFORMATION**
**Further information**
**NFPA:**

**HMIS III:**

<b>HEALTH</b>	<b>3*</b>
<b>FLAMMABILITY</b>	<b>3</b>
<b>PHYSICAL HAZARD</b>	<b>2</b>

0 = not significant, 1 = Slight,  
2 = Moderate, 3 = High  
4 = Extreme, \* = Chronic

**OSHA - GHS Label Information:**

Hazard pictograms



Signal word

: **Danger:**

Hazard statements

: Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure if inhaled.

Precautionary statements

: **Prevention:** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapours/spray. Wash skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.

**Response:** IF SWALLOWED: Immediately call a POISON CENTER/doctor. IF ON SKIN: Wash with plenty of soap and water. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/attention. Do NOT induce vomiting. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse.

**Storage:** Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

**Disposal:** Dispose of contents/container in accordance with local regulation.

**PROFESSIONAL RUBBERIZED COATING AERO**

Version 3.0

Revision Date 06/29/2017

Print Date 10/30/2017

Version:	3.0
Revision Date:	06/29/2017
Print Date:	10/30/2017

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.

Zep Inc. markets products under well recognized and established brand names such as Zep®, Zep Commercial®, Zep Professional®, Enforcer®, National Chemical™, Selig™, Misty®, Next Dimension™, Petro®, i-Chem®, TimeMist®, TimeWick™, MicrobeMax®, Country Vet®, Konk®, Original Bike Spirits®, Blue Coral®, Black Magic®, Rain-X®, Niagara National™, FC Forward Chemicals®, Rexodan®, Mykal™, and a number of private labeled brands.